



100 Bean Street
Clear Lake, WI 54005

tel 715.263.2112
800.628.6196

For your local dealer, visit:

www.oxbocorp.com



Specifications	
Transport width:	9ft 10in (3.0m)
Working width:	39ft 9in (12.12m)
Actual width:	33ft 11in (10.34m)
Transport length:	23ft 7.5in (7.2m)
Working length:	24ft 5in (7.44m)
Transport height:	12ft (3.66m)
Wheel base:	10ft 8in (3.25m)
Weight (full fuel):	28,240lb (12809kg)
Pickup	
Conveyor length:	Two 12ft (3.66m); One 10ft (3.05m)
Conveyor belt width:	3 ft (0.91m)
Strippers:	Poly
Rubber mounted teeth:	2" spacing
Tires	
Front:	700/50-30.5
Rear:	600/55-26.5
Track	
Front:	7ft 2in (2.18m)
Rear:	7ft 6.5in (2.3m)
Turning Radius:	92.5in (2.35m) (inside front tire)
General	
4WD, Low Range (Field mode)	0-17 mph (0-24.7 km/h)
4WD, High Range (Road mode)	0-30 mph (0-48.3 km/h)
General	
John Deere Engine:	6.8L, 250hp, turbocharged, Tier III, Liquid cooled



4334



self-propelled merger

U.S. Patents: 6,205,757; 6,935,488; 7,070,042; 7,310,929; 7,418,811; 7,628,004; 7,673,439; 7,823,371; 7,827,774; 8,091,331; 8,166,739; 8,186,138; 8,312,700; 8,402,730; 8,511,052. Patents Pending.
Descriptions and specifications subject to change without notice. ©2015 Oxbo International Corp., member of the Ploeger Oxbo Group
433415.pdf



4334

For over a decade, Oxbo has been the undisputed leader in merger technology and design. With the introduction of the 4334 self-propelled merger, Oxbo redefines the merger, offering new levels of windrow control, forage quality, and operator comfort. With front mounted pickup heads, the 4334 delivers:

- High quality windrows—never drive over cut crop
- Unprecedented windrow control
- Uniform windrows able to feed the appetite of the largest choppers
- Oxbo's patented pickup technology
- Ultimate operator comfort to reduce fatigue and improve forage quality

Ultimate control

- Front mounted heads for unmatched visibility
- Maximum control of windrow placement with conveyor on/off foot switch; other functions controlled from the joystick

Smooth ride shoes

- Innovative float system delivers smooth ground following
- Wide stance shoes provide a smooth ride over rocks or pivot tracks
- Shoes allow faster ground speed without header bounce and eliminate wheels, bearings, seals, axles, under conveyors

Driving productivity



- Rubber mounted split tines for excellent recovery in all crops
- Folds to a narrow 10-foot transport width in under 20 seconds
- 30mph road speed for fast transport between fields
- Single switch control to raise, lower, fold or unfold the heads
- Backed by Oxbo and your local dealer for the best parts and customer service in the industry

Easy-to-use controls: Adjust your merger on the fly with the ability to raise, lower, fold and unfold heads with a well positioned joystick and easy to use controls

Climate controlled cab: Features air ride seat and full visibility of all 34-feet of crop pick up; reduces driver fatigue and contributes to improved forage quality

Improved! 41-inch high wind guards: Keeps light crop on the conveyor

Quick fold heads: Heads fold quickly for a narrow, 10-foot transport width; steps to operator's platform fold up and out of the way



Center cam drive: Strong support, minimal gap between heads

Conveyor trough: Delivers uniform, consistently shaped windrow for smoother harvester feeding

NEW! Rubber mounted split tines: 2 inch spaced along full pick up width. Deliver excellent crop recovery with less rocks even in light or difficult crops



Wide shoes: Smooth head ride over rocks, chuck holes, pivot tracks, or ruts; eliminate header bounce

Hydraulic float system: Innovative float system incorporates a nitrogen filled accumulator assist and a dedicated set of cylinders for smooth ground following

Features

- **Full 34-foot header width:** Oxbo's patented design creates continuous pickup



- Powerful, 6.8L, 250hp Tier III engine boosts in field performance
- Reversing engine fan
- Full time 4-wheel drive: powers the merger through all field conditions
- Traction control on the rear axle for improved performance
- Belt seals on all conveyors

Options

- **High intensity light package:**



- **NEW! Auto Steer:** Reduces operator fatigue. Utilizes WAAS differential correction. Includes Ag Leader Versa display.

