



100 Bean Street
Clear Lake, WI 54005

tel 715.263.2112
800.628.6196
www.oxbocorp.com

Specifications	
Dimensions	
Length without header:	30ft 2in (9.2m)
Width without header:	11ft 3in (3.43m)
Height:	13ft 1in (3.99m)
Wheelbase:	13ft 8in (4.17m)
Track:	8ft 1in or 10ft (2.46m or 3.05m)
Inside turning radius:	12ft 9in (3.89m)
Weight without header:	30,500lbs (13,835kg)
Tires	
Size:	24.5 x 32 12 ply
Engine	
Engine:	Cummins 6.7L
Horsepower:	260hp
Dump Box	
Volume:	530 cu. ft. (15.00 cu.m.)
Dump box lifting capacity:	14,000 lbs (6,350kg)
Dump height to dump box lip (without extension):	8ft 8in - 14ft 6in (2.64m - 4.42m)
Tank Capacities	
Fuel:	240 gallons (908.5L)
Hydraulic reservoir:	60 gallons (227.1L)
Cooling system:	10.5 gallons (39.75L)
Crankcase:	5.0 gallons (18.9L)
Harvesting Head Capabilities	
Beans:	Oxbo VPC1500 (150 in, 4.14m width)
Beans:	Oxbo VPC 1800 (180 in, 4.57m width)
Fresh Market Sweet Corn:	Oxbo CP400 (4 rows)
Seed & Processed Sweet Corn:	Oxbo 3000 Series (6 row max)
Spinach & Greens:	Oxbo SP150 (150 in, 4.14m width)



2470



multi-crop harvester



2470

Based on the long-standing industry leading Big Jack, Oxbo specifically developed the 2470 as a next generation multi-crop harvester which delivers increased productivity, performance, reliability, operator comfort, and control. The Oxbo 2470 represents a new level of efficiency for sweet and seed corn, green bean, and other specialty vegetable harvesting operations.

The 2470 was designed to give you the performance your conditions demand: getting your crop in when it is ready, regardless of field conditions

Performance when it counts

- Four-wheel mechanical drive train for peak performance, even in mud
- 240 gallon fuel tank: 2470 can run a full 24-hours, at capacity, without stopping to refuel
- Six tons of beans per hour harvest capacity

Driving your productivity

- Hydraulics designed by Certified Fluid Power Engineers give you increased life span, maximum efficiency
- High capacity cooling to safeguard the systems, even in high temperature harvest conditions
- Transmission protected from driver error to reduce costly downtime
- Hydraulically adjusted fan hoods increase reliability and control

Innovation to move you forward

- Plus+1 microcontroller and monitoring system gives the operator instant feedback on each harvester system
- Electronic controls provide new levels of adjustment precision to maximize harvester productivity



Redesigned dump box: Dump at any height. Simplified design eliminates bell-cranks, links, and cables to reduce maintenance.

Premium product quality: Harvest high quality green beans, processed or fresh market sweet corn, and seed corn




High capacity cooling: Auxiliary cooler protects your investment and delivers longer pump and motor life cycle

Effective cleaning: Independent, dual controlled cleaning fans prove effective even in small grade beans

Legendary mudability: The same mudability that made the Super Jack the #1 choice for North American processors was incorporated into the 2470

Features

- **NEW** 14,000 pound dump box capacity
- Hydraulically actuated fan discharge chutes
- Dual motor, 34-in diameter cleaning fans with replaceable UHMW fan blades
- Fast and slow tilt cylinder dump for increase control of product transfer
- DP600 color monitor display with speed monitors and stall alarms for selected rotating functions



Options

- Live belted dump box floor to meter product flow in fresh market crops
- Flotation radial tires
- Reserving fan
- Dump box extension
- Heavy duty tow hitch



Versatile, multi-crop: Compatible with the CP400 fresh market corn head, processed corn heads, 120- or 150-inch bean heads, or a 150-inch spinach and greens head

