



blueberry harvester

Oxbo 930 Berry Harvester

Fruit Quality

The Oxbo 930 is a tow behind harvester that features a full sized picking tunnel to handle both large and small plants. The 930 features a single drop belt system to ensure the highest quality blueberries and its lightweight design requires only a small tractor:

- **Single drop harvester** Blueberries are conveyed to the back of the machine where they are cleaned and put into totes or lugs. Together the single drop and an effective cleaning system combine to help deliver the highest quality fruit.
- **Ultra Low Loss catcher design:** High density, Ultra Low Loss 4¾ inch spacing catchers have been proven to retain more fruit in blueberry harvesting than any other catcher design.
- **Solid stainless steel sides**
- **Low profile cane lifter design**



Harvester Quality

Designed and built in the USA to the highest manufacturing standards and to CE compliance, the Oxbo 930 has been built to give long lasting performance. Key components of the harvester, like catchers, buckets, and belts have been designed for a long life. Options include:

- Floatation package
- Power beater adjust
- 10 inch belt extension
- Top beater
- Food grade oil
- Automatic steering

Customize for Your Conditions

Not only does the Oxbo 930 give you reliability, but it also gives you more choice in picking systems:

- **Orbirotor® System:** The unique Orbirotor utilizes an orbital shaking action that is easily adjusted to meet a wide range of picking requirements. The selective shake lets you take advantage of the early season price by allowing you to get into the field earlier than you would with any other shaking system on the market. 
- **Dynarotor® System:** Dynarotor heads use a more aggressive horizontal shaking action, primarily used in blueberry harvesting. Weights can be added for a more aggressive pick for clean up. 
- **Sway System:** The 930 also offers a traditional sway system that removes fruit by swaying the plants back and forth as a group.

Specifications

Length:	17ft 10 in (5.44m)	Lift:	2ft 1in (0.64m)
Width:	10ft 5in (2.74m)	Tunnel Width:	2ft 9in (0.84m)
Min. Height:	9ft 4in (2.84m)	Inside Catchers:	2ft 2in (0.66m)
Weight:	5,600lbs (2,545kg)	Tires:	31 x 15.5 x 15




oxbo®

270 Birch Bay Lynden Road
Lynden, WA 98264

tel 360.354.1500
fax 360.354.1300
www.oxbocorp.com

© 2011 Oxbo International Corp.
93012.pdf